



SUGGESTED PCB LAYOUT  
TOP VIEW

**Electrical Characteristics :**

- Insulation Resistance : 500MΩ Min.
- Contact Resistance : 30mΩ Max.
- Withstand Voltage : 500 VAC 1 minute.
- Current Rating : 1.5A

**Material:**

Housing : Thermoplastic UL94V-0  
 Contact : Full Gold Plating  
 Spring Wire : Dia 0.45mm Phosphor Bronze  
 Optional Gold Plating Over Nickel  
 CUL File No : E215573

**PART NO : 7 0 6 8 - B \* 2 1**

RJ45 Positions  
 Housing Color  
 B : Black  
 Ports  
 Gold Plated  
 0 : 3u"±1u"  
 1 : 6u"±1u"  
 2 : 15u"±5%  
 3 : 30u"±5%  
 4 : 50u"±5%

# Wellco T&C Co., Ltd.

TITLE 圖名	SHIELDED SIDE ENTRY PCB JACK	UNIT 單位	mm inch
PART NO. 料號	7068-B * 2 1	SCALE 比例	1 : 1
REV. 版本	A.0 日期	DATE 日期	2008-02-18
CHECKED BY 審核	Michael	DRAWN BY 製圖	David

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 52 (SERIES)	TOLERANCE(公差) :
(A)						0.000 mm ± 0.075 mm
(B)						0.00 mm ± 0.15 mm
(C)						0.0 mm ± 0.25 mm
(D)						
(E)						