







SUGGESTED PCB LAYOUT
TOP VIEW

Electrical Characteristics :

- Insulation Resistance : 500MΩ Min.
- Contact Resistance : 30mΩ Max.
- Withstand Voltage : 500 VAC 1 minute.
- Current Rating : 1.5A

Material:
Housing : Thermoplastic UL94V-0
Contact : Full Gold Plating
Spring Wire : Dia 0.45mm Phosphor Bronze
Optional Gold Plating Over Nickel

PART NO : 5 4 4 4 - B ＊ 1

- Positions
- Contacts
- Housing Color
  B : Black
- Ports
- Gold Plated
  0 : 3u"±1u"
  1 : 6u"±1u"
  2 : 15u"± 5%
  3 : 30u"± 5%
  4 : 50u"± 5%

ZONE	REV.	DESCRIPTION	DATE	APPD.
Ⓐ				
Ⓑ				
Ⓒ				
Ⓓ				
Ⓔ				

FILE NO : 54 (SERIES)

TOLERANCE(公差) :
0.000 mm ± 0.075 mm
0.00 mm ± 0.15 mm
0.0 mm ± 0.25 mm

Wellco T&C Co., Ltd.

TITLE 圖 名	4P4C SIDE ENTRY PCB JACK			UNIT 單位	mm inch
PART NO. 料 號	5444-B＊1			SCALE 比 例	1 : 1
REV. 版本	A.0	DATE 日 期	2007-02-01		
CHECKED BY 審 核	Michael		DRAWN BY 製 圖	Valiant	