



RECOMMEND PCB LAYOUT

NOTES:

ELECTRICAL:

- 1. VOLTAGE RATING : 125VAC RMS
- 2. CURRENT RATING : 1.5 AMP
- 3. CONTACT RESISTANCE : 50 MILLIOHMS MAX
- 4. INSULATION RESISTANCE : 500 MEGOHMS MIN @500 VDC
- 5. DIELECTRIC STRENGTH : 1000 VAC RMS 50HZ.1MIN

MECHANICAL:

- 1. HOUSING MATERIAL : GLASS FILLED POLTER(U194V-0)
- 2. CONTACT MATERIAL : PHOSPHOR BRONZE T=0.46MM
- 3. PLATING : GOLD PLATION OVER NICKEL
- 4. OPERATION LIFE : 750 CYCLES MIN
- 5. PCB RETENTION PRE-SOLDER:1 LBMIN
- 6. PCB RETENTION POST-SOLDER:10 LBMIN

ENVIRONMENTAL:

- 1. STORAGE : -40°C TO +85°C
 - 2. OPERATION : 0°C TO +70°C
 - 3. WAVE SOLDER TEMPERATURE:230~250°C(5~10SECONDS)
- MATES WITH MODULAR PLUG CONFORMING TO FCC PART68 SUBPART F

PART NUMBER:

XARJ45+USBA-XXXXXXX

RJ45+USBA SERIES PCB JACK

(RJ45+USBA系列PCB接口)

- POSITIONS (特殊位):
- 4-4POSITIONS (4P). 6-6POSITIONS (6P)
- 8-8POSITIONS (8P). 0-10POSITIONS (10P)

- CONTACTS (特殊位):
- 2-2CONTACTS (2C)
- 4-4CONTACTS (4C). 6-6CONTACTS (6C)
- 8-8CONTACTS (8C). 0-10CONTACTS (10C)

- USB PORTS (接口):
- 1-1X1 (一单). 2-1X2 (二单)

- GOLD PLATING (镀金层):
- 1-FU". 2-3U". 3-6U".
- 4-15U". 5-30U". 6-50U".
- PLASTIC (塑料):
- 1-PBT. 2-NYLON66 (尼龙66)
- 3-NYLON46 (尼龙46). 4-ABS
- LED STYLE:
- 0-W/O LED (无LED) 1-W LED (有LED)
- SHIELD (屏蔽):
- 0-W/O SHIELD (无屏蔽) 1-HALF SHIELD (半屏蔽)
- 2-SHIELD W/EMI (有EMI屏蔽)
- 3-SHIELD W/O EMI (有EMI屏蔽)

REVISION RECORD

REV	ECO	DESCRIPTION	DRFT	CHKD
△		原始版本	MARRY 06.06.09	
△		增加料号,更改图号	JACKY 07.02.05	
△		增加颜色信息	ZHOUXIONG 07.04.28	

MM (INCH)		设计 MARRY	日期 06.06.09	Wellco T&C Co., Ltd.	
公差	±	审核 JACKY	日期 06.06.09	系列	名称 无滤波
.0 ± 0.20	±	批准 ZHOUXIONG	日期 06.06.09	RJ45+USBA	XARJ45+USBA-8813113
.00 ± 0.15	±	材料:		图号: XARJ45+USBA	版本 A4 版本
.000 ± 0.075	±	数量:		料号: 请查资料	第 1 页 共 1 页
角度 ± 0.01°		表面处理:		比例: 1:1	
第三角视图					
DETACHED LISTS					