

<p><b>1</b></p> <table border="1"> <tr> <th>REV.</th> <th>ECN. NO.</th> <th>NAME</th> <th>DATA</th> </tr> <tr> <td>A1</td> <td>NEW</td> <td>" # \$</td> <td>2011-12-27</td> </tr> <tr> <td>A2</td> <td>14H F G V W</td> <td>" # \$</td> <td>2012-04-06</td> </tr> </table>	REV.	ECN. NO.	NAME	DATA	A1	NEW	" # \$	2011-12-27	A2	14H F G V W	" # \$	2012-04-06	<p><b>2</b></p> <p>ELECTRICAL:          CURRENT RATING:1.5AMPS          VOLTAGE RATING:125V AC          INSULATION RESISTANCE:500M MINI          WITHSTAND VOLTAGE:AC 1000V RMS 50Hz OR 60Hz 1MIN          CONTACT RESISTANCE:20m MAX          MECHANICAL:          MATING FORCE: 2.2KG.F MAX          RETENTION STRENGTH:7.7KG.F BETWEEN JACK AND PLUG          DURABILITY:750MATING CYCLES MINI          MATERIAL:          HOUSING:LCP, UL94V0</p>	<p><b>3</b></p> <p>OPTIONAL          GOLD PLATING          GOLD PLATING: 3 INCH, 6 INCH, 15 INCH, 30 INCH, 50 INCH          METAL GASKET : 0.40mm THICKNESS, NICKEL PLATED COPPER</p>	<p><b>4</b></p> <p>ALLO(C2680)</p>	<p><b>5</b></p> <p>NOTES:          1. 端子:C5191-H T=0.35±0.01.          电镀半金锡</p>	<p><b>6</b></p> <p>2. 卡勾: C2680-EH T=0.40±0.01.          电镀镍底50u"亮锡120u"          3. 塑胶:LCP          4. 弹片750次插拔测试不下陷          5. 本产品符合RoHS环保要求          6. 标有"⊗"为FAI尺寸,标有"▽"号为重点管控及首件检测尺寸.</p>	<p><b>7</b></p> <p><b>Wellco T&amp;C Co., Ltd.</b></p> <table border="1"> <tr> <td>系列</td> <td>名称</td> </tr> <tr> <td>RJ</td> <td>RJ45 180% 8P8C&amp; ' (</td> </tr> <tr> <td>图号:</td> <td>!</td> </tr> <tr> <td>料号:</td> <td>A2</td> </tr> <tr> <td>单位:</td> <td>MM</td> </tr> </table> <p>共 1 页 第 1 页</p>	系列	名称	RJ	RJ45 180% 8P8C& ' (	图号:	!	料号:	A2	单位:	MM
REV.	ECN. NO.	NAME	DATA																									
A1	NEW	" # \$	2011-12-27																									
A2	14H F G V W	" # \$	2012-04-06																									
系列	名称																											
RJ	RJ45 180% 8P8C& ' (																											
图号:	!																											
料号:	A2																											
单位:	MM																											
<p><b>1</b></p>	<p><b>2</b></p>	<p><b>3</b></p>	<p><b>4</b></p>	<p><b>5</b></p>	<p><b>6</b></p>	<p><b>7</b></p>																						
<p><b>1</b></p>	<p><b>2</b></p>	<p><b>3</b></p>	<p><b>4</b></p>	<p><b>5</b></p>	<p><b>6</b></p>	<p><b>7</b></p>																						
<p><b>1</b></p>	<p><b>2</b></p>	<p><b>3</b></p>	<p><b>4</b></p>	<p><b>5</b></p>	<p><b>6</b></p>	<p><b>7</b></p>																						
<p><b>1</b></p>	<p><b>2</b></p>	<p><b>3</b></p>	<p><b>4</b></p>	<p><b>5</b></p>	<p><b>6</b></p>	<p><b>7</b></p>																						

7Q 9H F G R S % 0.08mm T U

PCB LAYOUT/TOP VIEW

设计: " # \$	审核:	批准:	材料:	数量:	表面处理:	比例: 1:1
一般公差栏	±	±	±	角度 ± 1.6°	第三角视图	
0.0 ± 0.20	0.00 ± 0.15	0.00 ± 0.075				

系列	名称
RJ	RJ45 180% 8P8C& ' (
图号:	!
料号:	A2
单位:	MM