

SPECIFICATION NOTES:

ELECTRICAL:

1. VOLTAGE RATING: 125 VAC RMS
2. CURRENT RATING: 1.5 AMP
3. CONTACT RESISTANCE: 30mΩ MAX.
4. INSULATION RESISTANCE: 1000MΩMIN. AT 500V DC.
5. DIELECTRIC STRENGTH: 1000 VAC 50Hz 1MINUTE

MECHANICAL:


1. HOUSING/INSERT MATERIAL: THERMOPLASTIC, LCP/NYLON UL94V-0 RATED, COLOR BLACK.
2. CONTACT MATERIAL: C5191-H T=0.30MM
3. SHELL MATERIAL: C2680-H T=0.20MM.
4. PLATING: GOLD PLATING OVER NICKEL, PLATED NICKEL 30-50U", SN 100-120U. GOLD PLATED ON CONTACT AREA FU/3U/6U/15U/30U". SHELL PLATING: PLATED NICKEL 30-80U".
5. OPERATING LIFE: 750 CYCLES MIN.
6. MATING FORCE: 5-25N UNMATING FORCE: 76N MIN.

ENVIRONMENTAL:

1. STORAGE: -40°C TO +85°C
2. OPERATION: -40°C TO +85°C

Recommend PCB Layout
(Jack Top View)
TOLERANCES: ±0.05

序号	品名规格	料号	LED
1	RJ45 8P8C 15.5 SMT 全包 无弹 FU" 无PHC	1060-208059	左黄右绿
2			
3			
4			

Gen. Tolerance	Scale	Not
.X ± 0.20	Unit	mm
.XX ± 0.08	Size	
.XXX ± 0.05		
<±1°		

Wellco T&C Co., Ltd.



P/N # 1060-208059
RJ45 8P8C 15.5 SMT

This spec drawing is
under the property of
Wellco T&C Co., Ltd.

Rev. A

Page 1-1

DRW by
CHK by
APP by

Amy July 07 2011
Long July 11 2011
Chin July 11 2011