







SUGGESTED PCB LAYOUT  
TOP VIEW

Electrical Characteristics :

- Insulation Resistance : 500MΩ Min.
- Contact Resistance : 30mΩ Max.
- Withstand Voltage : 500 VAC 1 minute.
- Current Rating : 1.5A

Material:

Housing : Thermoplastic UL94V-0  
 Contact : Full Gold Plating  
 Spring Wire : Dia 0.45mm Phosphor Bronze  
 Optional Gold Plating Over Nickel  
 CUL File No : E215573

PART NO : 8 2 8 8 - B \* 4 - R - L

Positions  
 Contacts  
 Housing Color  
 B : Black

Nylon Ports  
 Gold Plated  
 0 : 3u"±1u"  
 1 : 6u"±1u"  
 2 : 15u"± 5%  
 3 : 30u"± 5%  
 4 : 50u"± 5%

# Wellco T&C Co., Ltd.

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 82 (SERIES)
(A)					TOLERANCE(公差) : 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm
(B)					
(C)					
(D)					
(E)					

TITLE 圖名	NON-SHIELDED RJ45 SIDE ENTRY PCB JACK		UNIT 單位	mm inch
PART NO. 料號	8288-B * 4-R-L		SCALE 比例	1 : 1
REV. 版本	A.0	DATE 日期	2007-01-05	
CHECKED BY 審核	Michael		DRAWN BY 製圖	Valiant