

Electrical Characteristics :

- Insulation Resistance : 500MΩ Min.
- Contact Resistance : 30mΩ Max.
- Withstand Voltage : 500 VAC 1 minute.
- Current Rating : 1.5A

Material:

Housing : Thermoplastic UL94V-0

Contact : Full Gold Plating

Spring Wire : Dia 0.45mm Phosphor Bronze


Optional Gold Plating Over Nickel

Shield : Brass, Nickel Plating.

CUL File No : E215573

PART NO : 8 3 8 8 A S - B * 1 *

- Positions
- Contacts
- Panel Ground
- S : 3Sides With Panel Ground
- Housing Color
- B : Black
- Gold Plated
- 0 : 3u"±1u"
- 1 : 6u"±1u"
- 2 : 15u"±5%
- 3 : 30u"±5%
- 4 : 50u"±5%



Wellco T&C Co., Ltd.

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 83 (SERIES)	TITLE	SHIELDED RJ45 SIDE ENTRY PCB JACK		UNIT	mm	
(A)					TOLERANCE (公差) : 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm	圖名			單位	inch	
(B)						PART NO.	8388AS-B * 1 *		SCALE	1 : 1	
(C)						料號			比例		
(D)						REV.	A.0	DATE	2007-07-17		
(E)						版本		日期			
						CHECKED BY	Micheal		DRAWN BY	Valiant	
						審核			製圖		

