



- Electrical Characteristics :**
- Insulation Resistance : 500MΩ Min.
 - Contact Resistance : 30mΩ Max.
 - Withstand Voltage : 500 VAC 1 minute.
 - Current Rating : 1.5A

Material:
 Housing : Thermoplastic UL94V-0
 Contact : Full Gold Plating
 Spring Wire : Dia 0.45mm Phosphor Bronze
 Optional Gold Plating Over Nickel
 CUL File No : E215573

PART NO : 5 2 8 8 - B * *



Dimensions	No. Of Ports							
	4	5	6	7	8			
A	60.9	75.4	89.9	104.4	118.9			
B	58.5	73.0	87.5	102.0	116.5			
C	43.5	58.0	72.5	87.0	101.5			

Wellco T&C Co., Ltd.

ZONE	REV.	DESCRIPTION	DATE	APPD.
(A)				
(B)				
(C)				
(D)				
(E)				

FILE NO : 52 (SERIES)
 TOLERANCE(公差) :
 0.000 mm ± 0.075 mm
 0.00 mm ± 0.15 mm
 0.0 mm ± 0.25 mm

TITLE	MULTI-PORTS RJ45 SIDE ENTRY PCB JACK	UNIT	mm
圖名		單位	inch
PART NO.	5288-B * *	SCALE	1 : 1
料號		比例	
REV.	A.0	DATE	2007-04-14
版本		日期	
CHECKED BY	Michael	DRAWN BY	Valiant
審核		製圖	