



SUGGESTED PCB LAYOUT
TOP VIEW

- Electrical Characteristics :
- Insulation Resistance : 500MΩ Min.
 - Contact Resistance : 30mΩ Max.
 - Withstand Voltage : 500 VAC 1 minute.
 - Current Rating : 1.5A

Material:

Housing : Thermoplastic UL94V-0

Contact : Full Gold Plating

Spring Wire : Dia 0.45mm Phosphor Bronze

Optional Gold Plating Over Nickel

CUL File No : E215573

PART NO : 8 1 0 8 N - B * 1 *



LED Color Options Table

LED 2 (Left)	LED 1 (Right)	LED DASH OPTION
No LED	No LED	0
Yellow	Green	1
No LED	Green	2
Yellow	No LED	3
Green	Yellow	4
Green	Green	5
Yellow	Yellow	6
Orange/Green	Orange/Green	7
Yellow/Green	Yellow/Green	8
Orange/Green	Yellow	9
Green	Orange	A
Orange	Green	B
Green	Red	C
Red	Green	D

Wellco T&C Co., Ltd.

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 81 (SERIES)
(A)					TOLERANCE(公差) :
(B)					0.000 mm ± 0.075 mm
(C)					0.00 mm ± 0.15 mm
(D)					0.0 mm ± 0.25 mm
(E)					

TITLE	NON-SHIELDED RJ45 SIDE ENTRY PCB JACK	UNIT	mm
圖名		單位	inch
PART NO.	8108N-B * 1 *	SCALE	1 : 1
料號		比例	
REV.	A.0	DATE	2007-11-30
版本		日期	
CHECKED BY	Michael	DRAWN BY	Valiant
審核		製圖	