

REV.	ECN.NO.	DATE
A	RELEASED	01/06-'07

Notes:

*Material

Housing: LCP, UL 94V-0 rated;
 Color: Black.
 Contact: Phosphor Bronze
 Plating: Gold Plating over Nickel on contact area
 Tin plating on solder Tail.

*Mechanical

Insertion Force: 45N max.
 Withdrawal Force: 10N min.
 Durability: 500 cycles

*Electrical Specification

Operation Voltage: 100 VAC max.
 Current Rating: 1.5 Ampere per contact
 Contact Resistance: 30 Milliohms max.
 Insulation Resistance: 1000 Megohms min.
 Dielectric Withstanding Voltage: 500 VAC

*Environmental

Operating Temperature: -55°C to +125°C

*How to Order:

WATB 22 D L 1 P B U
 Blank: No Mark
 U: Lead Free
 B: Dip Type (high 4.30mm)
 P: Phosphor Bronze
 1: Black
 L: LCP
 Selective Gold: D:15u" A:Flash
 NO. of Contacts
 Series No.

REV	Units	mm	Scale	2:1	Drawing By	Data	Wellco T&C Co., Ltd.			
					WHL	01/15-'07	Date	01/06-'07	Sheet	1 of 1
					Reviewed By	Jflee	Data	01/15-'07	Third Angle Projection	Title
					Approval By	Richard	Data	01/15-'07	Drawing No.	W070106
									REV	A

P.C.B LAYOUT (T=1.2)
 TOP VIEW

